

**PM811**

*Boxed Power Supply 12 VDC - 1 A*



**Kenmerken**

- **Fault and mains present indicators**
- **Tamperswitch**
- **Mains and dc fuse**
- **Fully compliant with IEC65**
- **Transformers conform to BS145, VDE0550 & UL506**
- **Powder coated steel housing**



# PM811

Boxed Power Supply 12 VDC - 1 A

## Technische gegevens

<b>Input voltage</b>	230 VAC
	50 Hz $\pm$ 10%
<b>Output voltage</b>	13.8 VDC
<b>Load output</b>	0.5 A
<b>Total output</b>	1 A
<b>Output ripple</b>	Max. 50 mVrms
<b>Max. battery size</b>	7.2 Ah
<b>Battery recharge time</b>	24
<b>Battery disconnect voltage</b>	-
<b>Open collector output</b>	-
	-
	-
<b>Fuse 12/24 V output</b>	1.25 A
<b>Fuse 230 VAC input</b>	2 A
<b>Operating temperature</b>	-10 °C to +40 °C
<b>Relative humidity</b>	95%
<b>Housing (steel) powder coated</b>	1.2 mm
<b>Dimensions (H x W x D)</b>	200 x 230 x 80 mm

## Bestelinformatie

Type nummer	Omschrijving
PM811	Boxed power supply 12 VDC - 1 A



**GE Security**

[www.gesecurity.nl](http://www.gesecurity.nl)